



THREE-PHASE SYNCHRONOUS GENERATOR 20141201

Datasheet For 50Hz @ 1500rpm / 60Hz @ 1800rpm

EG225-80N

Frequency	Hz	50				60					
Rated capacity (kVA)	S	95.0	100.0	103.8	110.0	104.5	110.0	114.4	121.0	126.5	132.0
Rated power (kW)	P	76	80	83	88	83.6	88	91.5	96.8	101.2	105.6
Voltage (V)	U	380	400	415	440	380	400	416	440	460	480
Short-circuit ratio	Kcc	0.468	0.541	0.619	0.8	0.321	0.342	0.361	0.395	0.43	0.487
Reactance											
Direct axis synchronous reactance	Xd	2.641	2.509	2.418	2.28	3.486	3.311	3.183	3.01	2.879	2.759
Direct axis transient reactance saturated	X'd	0.099	0.094	0.091	0.086	0.131	0.124	0.119	0.113	0.108	0.104
Direct axis subtransient reactance saturated	X''d	0.092	0.087	0.084	0.079	0.121	0.115	0.11	0.104	0.1	0.096
Quadrature axis synchronous reactance	Xq	1.202	1.142	1.1	1.038	1.586	1.507	1.449	1.37	1.311	1.256
Quadrature axis subtransient reactance	X''q	0.155	0.147	0.142	0.134	0.204	0.194	0.187	0.177	0.169	0.162
Negative sequence reactance saturated	X2	0.12	0.12	0.11	0.11	0.16	0.15	0.15	0.14	0.13	0.13
Zero sequence reactance unsaturated	X0	0.005	0.004	0.004	0.004	0.006	0.006	0.005	0.005	0.005	0.005
Time constant											
Open circuit time constant	T'd0	1.261	1.261	1.261	1.261	1.26	1.26	1.26	1.26	1.26	1.26
Short-circuit transient time constant	T'd	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047
Subtransient time constant	T''d	0.002	0.002	0.002	0.002	0.002	0.002	0.002	0.002	0.002	0.002
Armature time constant	Ta	0.008	0.008	0.008	0.008	0.008	0.008	0.008	0.008	0.008	0.008
No load losses	W	1268	1335	1388	1480	1664	1724	1774	1853	1922	1994
Heat dissipation at full load at Class H	W	8344	8761	9231	10489	9950	9746	9995	9993	10191	10590
Efficiency											
PF=0.8 Efficiency of 25% load	%	91.19	90.71	90.16	88.75	91.63	91.66	91.50	91.38	91.17	90.79
50% load	%	92.43	92.22	91.90	90.98	93.12	93.36	93.37	93.49	93.49	93.33
75% load	%	91.60	91.53	91.32	90.60	91.69	92.11	92.24	92.52	92.65	92.61
100% load	%	90.11	90.13	89.99	89.35	89.36	90.03	90.15	90.64	90.85	90.89
110% load	%	89.12	89.19	89.08	88.47	87.92	88.59	88.83	89.35	89.63	89.73
PF=1 Efficiency of 25% load	%	92.19	91.76	91.29	90.10	92.73	92.63	92.45	92.31	92.11	91.84
50% load	%	94.18	94.02	93.80	93.18	95.25	95.33	95.31	95.39	95.37	95.32
75% load	%	94.01	93.99	93.90	93.52	94.75	94.97	95.04	95.27	95.38	95.46
100% load	%	93.23	93.31	93.30	93.08	93.50	93.84	93.94	94.32	94.51	94.72
110% load	%	92.57	92.70	92.72	92.55	92.40	92.79	92.97	93.40	93.65	93.89
No load excitation current	io(A)	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Full load excitation current	ic(A)	3	3	3	3	3	3	3	3	3	3
Full load excitation voltage	uc(V)	23	23	23	23	23	23	23	23	23	23
Short circuit current capacity	%	>300I _N 10s(with PMG or Auxiliary winding)									
Recovery time	Tr	1s									
Waveform : TIF		<50									
Waveform : THD		<3%									
Waveform : THF		<2%									
Winding pitch		2/3									
Steady state voltage regulation		+/-1%									
A.V.R. model		EVC300									
Duty		Continuous									
Number of poles		4									
Class of insulation		H									
Altitude		≤1000m									
Rated power factor		0.8									
Excitation		Brushless									
Stator winding		12ends									
Rotor		With damping cage									
Overload	%	110% rated load for 2 hour per 24 hour									
Stator winding resistance (20°C)	ohm	0.0466	0.0466	0.0466	0.0466	0.0466	0.0466	0.0466	0.0466	0.0466	0.0466
Rotor winding resistance (20°C)	ohm	0.391	0.391	0.391	0.391	0.391	0.391	0.391	0.391	0.391	0.391
Exciter resistance (20°C)	ohm	7.118	7.118	7.118	7.118	7.118	7.118	7.118	7.118	7.118	7.118
Cooling air requirement	m ³ /min	22.3	22.3	22.3	22.3	26.8	26.8	26.8	26.8	26.8	26.8
Energy storage constant (H)	sec.	0.147	0.140	0.134	0.127	0.192	0.183	0.176	0.166	0.159	0.152
Method of cooling		IC 01									
Ambient temperature		40°C									
Sense of rotation		Clockwise-DE									
Type of construction		Single / Double bearing									
Degree of protection / enclosure		IP21 or IP23									
Maximum overspeed		2250 rpm 2minutes									